

Multi-Purpose Lifting Machine



- A semi-permanent life, preventing it from being pushed back upon stopping a back-piece
- With a touchscreen / emergency switch / voice enabled monitoring system
- Minimizing confusion by adopting a joystick that is easily operable.
- Excellent safety even in left and right stop
- It has emergency stop and safety functionality
- Can be used for Spraying, Pruning, Bagging, Harvesting, and Transporting.

Features

SMART CONTROL SYSTEM

Touchscreen / Emergency Switch / Voice Enabled Monitoring System

LOW-CENTERED GRAVITY DESIGN

Excellent safety even in left and right stop

AC MOTOR

A semi-permanent life, preventing it from being pushed back upon stopping a back-piece

OPTIMAL STABILITY

Distribution of loads on the entire track / excellent stability

EMERGENCY STOP

Emergency Stop and Safety Functionality

SIMPLE OPERATION

Minimizing confusion by adopting a joy stick that is easily operable

UPGRADED SUSPENSION

A structure preventing deviation from the track and minimizing vibration

COMMUNICATION SYSTEM

Checking communication between controllers / easy to take quick measures for customer services

Specifications

Model	Agricultural Machinery		Multi-crop Lifter
	Name		SB-8500
Dimensions	Length (mm)		2699
	Width (mm)		1500
	Height (mm)		2200
	Weight (kg)		1530
Motor and Drive	Operating type		Caterpillar track (Motor drive)
	Track width x pitch x link		200 x 72 x 50 EA
	Motor type		DC 48V 2.0 kW x 2 set
	Steering type		Joystick lever
	Speed (km/h)	Forward	0 - 3.0
		Reverse	0 - 3.0
Hydraulic system type		Hydraulic power pack (Maximum oil pressure 15 MPa)	
Maximum load (kg)		100	
Work platform	Turning angle (°)		270
	Work platform minimum height (mm)		600
	Work platform maximum height (mm)		5500
Hydraulic power		Powerpack type (Max. 15 MPa)	

* These specifications above to change for enhancements in quality and performance.

Power Transport Vehicle

- Simple operability
- Forward 3rd, Reverse 2nd
- Powerful 8 horsepower engine
- 3 sides of the loading box open
- Multipurpose for (agriculture, livestock, fisheries, industry)



Features



Dump and lift conversion with simple lever operation



Automatic opening of rear door when dumping



side door extendable



Atomizer can be installed
*Atomizer die can be purchased separately



Generous size that can load 6 boxes of 20kg (based on 600tld)



Emergency stop switch that can safely turn off the engine in emergency situations

Specifications

Model	Agricultural Machinery	
	Name	
	Power Transport Vehicle	
	TK-600TLD	
	Agricultural Power Carrier	
	Machine type name	Agricultural Power Carrier
	Load box size (mm)	1140 x 1085 x 250
	Loading weight (kg)	500
	Lift height (mm)	1330
	Engine power (kW)	5.9 (Gasoline)
	Number of rows/row spacing (mm)	Forward 1st stage: 1.3 / 2nd stage: 2.5 / 3rd stage: 4.3
		Reverse 1st stage: 1.3 / 2nd stage: 2.6
Dimensions	Length (mm)	2035
	Width (mm)	1225
	Height (mm)	1235
	Weight (kg)	455

* The specifications above are subject to change without pre-notice.